

SPECIFICATION : BAT-3HS (HDMI to HD-SDI)

Parameter	Typ.
Supported Video Formats	720(1440) x 480i @ 59.94/60, 720(1440) x 576i @ 50 1280 x 720p @ 50, 1280 x 720p @ 59.94/60 1920 x 1080i @ 50, 1920 x 1080i @ 59.94/60 1920 x 1080p @ 23.94/24, 1920 x 1080p @ 25, 1920 x 1080p @ 29.97/30 1920 x 1080p @ 50, 1920 x 1080p @ 59.94/60
Video Inputs	HDMI with embedded audio & auto mute when DVI input
Video Outputs	SMPTE- 259/272/274/292/296/299/424/425 3G/HD/SD-SDI, 2 x BNC
Audio Outputs	Supports 8 audio channels (4 stereo pairs) - when the input audio sample rate is 48kHz - Supports 2 audio channels (1 stereo pair) - Auto detection of the input audio sample rate



SPECIFICATION : BAT-3SH (HD-SDI to HDMI)

Parameter	Typ.
Supported Video Formats	720(1440) x 480i @ 59.94/60, 720(1440) x 576i @ 50 1280 x 720p @ 50, 1280 x 720p @ 59.94/60 1920 x 1080i @ 50, 1920 x 1080i @ 59.94/60 1920 x 1080p @ 23.94/24, 1920 x 1080p @ 25, 1920 x 1080p @ 29.97/30 1920 x 1080p @ 50, 1920 x 1080p @ 59.94/60
Video Inputs	3G, HD, and SD-SDI (auto-selected), SMPTE- 259/272/274/292/296/299/424/425 1x BNC input, 1x BNC loop-through output
Video Outputs	HDMI v1.3a, 24/30/36 bits per pixel, RGB, 2.25Gbs, SD, HD, 1080p50/60 HDMI Standard Type A connector
Audio Outputs	HDMI embedded audio, 24 bit, 2 or 8 channels RCA-style analog outputs at -10dBV



SPECIFICATION : BAT-SA (HD-SDI to Analog)

Parameter	Typ.
Supported Video Formats	720(1440) x 480i @ 59.94/60, 720(1440) x 576i @ 50 1280 x 720p @ 50, 1280 x 720p @ 59.94/60 1920 x 1080i @ 50, 1920 x 1080i @ 59.94/60 1920 x 1080p @ 23.94/24, 1920 x 1080p @ 25, 1920 x 1080p @ 29.97/30
Video Inputs	HD and SD-SDI (auto-selected), SMPTE- 259/272/274/292/296/299/424/425 1x BNC input, 1x BNC loop-through output
Video Outputs	Selectable Component (YPbPr) or Composite (CVBS and S-Video) by DIP switch NTSC and PAL support 3x BNC output
Audio Outputs	2 channels RCA-style analog outputs at -10dBV



SPECIFICATION : BAT-AS (Analog to HD-SDI)

Parameter	Typ.
Supported Video Formats	720(1440) x 480i @ 59.94/60, 720(1440) x 576i @ 50 1280 x 720p @ 50, 1280 x 720p @ 59.94/60 1920 x 1080i @ 50, 1920 x 1080i @ 59.94/60 1920 x 1080p @ 23.94/24, 1920 x 1080p @ 25, 1920 x 1080p @ 29.97/30
Video Inputs	HD Component (YPbPr) or SD Component/Composite/S-Video, 3x BNC
Video Outputs	SMPTE- 259/272/274/292/296/299 HD/SD-SDI with embedded audio outputs, 1 x BNC
Audio Outputs	2 channels unbalanced, 2x RCA
Video ADC	12-Bits
Audio Outputs	24-Bits, 48kHz

