

# Christie

## UHD982-P-A

Brilliant large-format  
4K UHD display



### Technical specifications Christie UHD982-P-A

Display technology	screen size (diagonal)	• 98" (247.69cm)
	native resolution	• UHD 3840 x 2160 (16:9)
	backlight	• Direct-lit LED
	LED lifespan	• 50,000 hours to 50% brightness
	display orientation	• Portrait and landscape
	pixel pitch	• 0.57 x 0.57mm
	bezel width (bottom/side/top)	• 21.4 mm
	brightness	• 350 nits (cd/m <sup>2</sup> ) typical • 400 nits (cd/m <sup>2</sup> ) max
	contrast ratio (full field)	• 1200:1 typical
	viewing angle (CR 10:1)	• 178° Vert., 178° Hor. (89U/89D/89L/89R) @ CR>10
	refresh rate	• 60Hz
	response time	• 8ms typical
	color space (CIE 1931)	• 72%
	display colors	• 1.07 billion colors (8 bit+FRC)
Video	inputs	• 4 x HDMI™ (Ver 2.0, HDCP 2.2) • DisplayPort™ (Ver 1.2a, HDCP 1.3) • USB-C • VGA • 2 x USB 2.0 • OPS
	outputs	• DisplayPort 1.2a • HDMI 2.0
Audio	inputs	• RCA (L/R) line in
	outputs	• 3.5mm headphone / audio line out • SPDIF optical out
Control	inputs	• RS-232 (D-Sub9) • LAN (RJ45) • IR wire extender
	outputs	• None
Power	input rating	• 100-240 VAC @ 50/60Hz
	power consumption	• 254W typical (without OPS) • <=3W in standby (with OPS)
Environment	operating temperature	• 32-104°F (0-40°C)
	storage temperature	• -4-140°F (-20-60°C)
	operating humidity	• 20-90% RH non-condensing
Physical	size (panel only)	• (WxHxD) 86.1 x 48.9 x 3.7" (2188 x 1243 x 93mm)
	weight	• 220.5lbs (100kg)
	mounting	• VESA 800mm x 400mm, M8
Runtime	• Designed for 24/7 operation featuring a reliable power supply <sup>1</sup>	
Features	• Commercial-grade LCD with direct-lit LED backlight • OPS slot • Anti-glare treatment • 2 x 12W speakers • On/Off scheduler • USB playback of Photo/Video/MP3 • HDMI-CEC • Crestron® Connected • Source switching for failover • Wi-Fi® <sup>2</sup> • Miracast device connectivity <sup>2</sup> • Pixel shifting	
Accessories	• Panel ships with IR remote control • External IR receiver • Power cable • Product safety guide	
Warranty	• Three years parts and labor limited warranty • Contact an authorized Christie representative for full details of our limited warranty	

<sup>1</sup> Avoid static images for extended periods. Refer to the user manual for additional runtime guidelines.

<sup>2</sup> WiFi capability is provided via USB dongle.

Content and operating conditions can affect the useful life of the product. Please refer to the product user manual and Christie Operating Guidelines for Flat Panels, available at [www.christiedigital.com](http://www.christiedigital.com)

For the most current specification information, please visit [christiedigital.com](http://christiedigital.com)

Copyright 2021 Christie Digital Systems USA, Inc. All rights reserved. All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. "Christie" is a trademark of Christie Digital Systems USA, Inc., registered in the United States of America and other countries. DLP® and the DLP logo are registered trademarks of Texas Instruments. Performance specifications are typical. Due to constant research, specifications are subject to change without notice. CD2107\_Christie UHD982-P-A\_Access II Series\_SpecSheet\_July-21\_EN



**CHRISTIE**®